Ucanpower, Bring Energy to Life!

CAN POWER

UFox-X
Off-Grid Energy Storage System



UFox-X series is an off-grid energy storage system, which can connect solar panel,grid（or generator) and load.

It contains expandable LFP battery, off-grid inverter and battery management system（BMS）.

It has multiple work modes to meet lots of application scenarios, and reduce the electricity bill, store the energy for emergency back-up.



High Reliability


- LFP battery cell technology, safe than ever.
- Multiple protections,safe and reliable.

User-Friendly

- Multi-purpose AC outlet,easy to use.
- Multiple work modes, meet lots of scenarios.

Advanced Design

- Both PV and grid charge, fast and convenient.
- Peak-shaving mode, reduce the electricity bill.
- Modular and all in one design, compact and elegant appearance, battery is expandable.



Upower Electric Co., Ltd
Tel: +86-755-28263405 Email: info@ucanpower.com Web: www.ucanpower.com

UcanPower GmbH
Tel: +49 (0) 170 4910717 Email: UcanPower.de@ucanpower.com

Model	UFox-X-070ES	UFox-X-100ES
Inverter		
Rated output power	7000W	10000W
Ouptut surge power	14000W,5s	20000W,5s
Max. output current	32A	45.4A
Rated output voltage	220/230/240V	
Rated frequency	50/60Hz	
THDv	<3%	
Output wave	Pure Sine Wave	
Output type	Pluggable connector	
AC input voltage range	170~280V	
AC input frequency	50/60Hz	
AC charge current per Inverter(Battery)	30A(0~60A) Adjustable	30A(0~80A) Adjustable
Max. PV power(Recommended)	4500W*2	6000W*2
Max. PV voltage	450V	
MPPT voltage range	120~430V	
Max PV charge current(Battery)	80A*2	100A*2
Weight	35kg	
Dimension [W x D x H]	620*365*256 mm	
Battery module		
Rated battery voltage	51.2V	
Battery voltgae range	44.8~57.6V	
Capacity	5.12 kWh	
Max. charge and discharge rate	1C	
Battery type	Li-ion（LFP）	
Weight	46.6kg	
Dimension [W x D x H]	620*365*139mm	

System Parameters							
System Structure							
Rated output power	7000/10000 W						
Number of battery	2	3	4	5	6	7	8
Battery capacity	10.24 kWh	15.36 kWh	20.48 kWh	25.6 kWh	30.72 kWh	35.84 kWh	40.96 kWh
Operating temperature	0℃~50℃ (Charge) / -10℃~50℃ (Discharge)						
Storage temperature	-15~60℃						
Humidity	5%~95%						
Cooling strategy	Fan						
Enclosure protection rating	IP20						
Communication	WiFi/RS485						
Weight	133.6 kg	180.2 kg	226.8 kg	273.4 kg	320 kg	366.6 kg	413.2 kg
Dimension [W x D x H]	620*365*631 mm	620*365*770 mm	620*365*909 mm	620*365*1048 mm	620*365*1187 mm	620*365*1326 mm	620*365*1465 mm
Certificate							
Certificate	CE,UN38.3,TUV mark						

Information may be subject to change without notice during product improving.

Upower Electric Co., Ltd

Tel: +86-755-28263405 Email: info@ucanpower.com Web: www.ucanpower.com

UcanPower GmbH

Tel: +49 (0) 170 491 0 717 Email: UcanPower.de@ucanpower.com